



Typ	EVO X40	X-403/1	X-403/2	X-603/1	X-603	X-903	X-1203	Plas-MIG 40/233
Netzspannung, 3-ph. [V/Hz]	230V/50Hz	400V/50Hz.	400V/50Hz.	400V/50Hz	400V/50Hz	400V/50Hz	400V/50Hz	400V/50Hz
Netzabsicherung (träge) [A]	16	16	16	16	25	32	33	25
Einstellungen	stufenlos	1	2	1	2	2	2	1 7
Leerlaufspannung V	350	350	350	270	270	280	280	280 36
Schneidstrom [A]	40	40	25 / 40	60	35 / 60	45 / 90	65 / 130	40 230
Schneidbereich [mm]	10	10	10	15	15	20	32	10
Einschaltdauer [A/%]	25 A/35%	40A/35%	40A/35% 25A/60%	60A/35%	60A/35% 35A/100%	90A/35% 45A/100%	130A/35% 65A/100%	40A/35% 230A/35%
Leistung [kVA]	3,6	8	8	15	15	22	15,5 / 10	8 10
Maße ca. (LxBxH) [mm]	450x190x520	275x385x470	275x385x470	560x770x540	560x770x540	560x770x540	650x840x650	850 x 420 x 620
Gewicht [kg]	15	30	30	71	77	89	130	112
Artikelnummer	03949	13010	13015	13001	13000	13050	13060	01571