



Typ	D L 140	D L 140 turbo	D L 200 turbo	D L 230 turbo	D L 260 turbo	D L 300 turbo
Netzspannung, 1/3-ph [V/Hz]	230/50	230/50	230/50 1-ph. / 400/50 2-ph.	230/50 1-ph. / 400/50 2-ph.	230/50 1-ph. / 400/50 2-ph.	230/50 1-ph. / 400/50 2-ph.
Netzabsicherung (träge) [A]	16	16	230 V/16 400 V/20	230 V/16 400 V/25	230 V/20 400 V/25	230 V/20 400 V/25
Regelbereich [A]	25-130	25-130	25-140	25-140	25-160	25-160
Schweißstrom bei 230 V	18 - 44	18 - 44	20 - 49	20 - 49	20 - 49	20 - 50
Schweißstrom bei 400 V	-	-	60-200	70-230	80-260	90-300
Schweißstrom ED [A/%]	130 A /20 %	130 A /25%	200 A /35 %	230 A /35 %	260 A /35 %	300 A /35 %
Zündspannung [V]	46 V, max.	46 V, max.	68 V, max.	68 V, max.	68 V, max.	68 V, max.
Kühlart	F	F	F	F	F	F
Isolierklasse	F	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21	21
Maße ca. (LxBxH) [mm]	350 x 250 x 260	350 x 250 x 260	470 x 275 x 385	470 x 275 x 385	470 x 275 x 385	470 x 275 x 385
Gewicht [kg]	20	21	38	40	44	48
Artikelnummer	03300	03301	03302	03304	03307	03309