



Typ	150 We 150 We-IP	190 Co 190 Co-IP	180 A 180 A-IP	200 A 200 A-IP	TWIN Mig Lotus 200 (löten und schweißen)	TRI Mig Lotus 200 (löten und schweißen)
Netzspannung, 1/3-ph [V/Hz]	230/50	230/50 1-ph. 400/50 2-ph.	400/50	400/50	400/50	400/50
Netzabsicherung (träge) [A]	16	16	16	16	16	16
Einstellungen, Stufen	6	6 + 6	7	7	7 + 7	7 + 7
Leerlaufspannung [V]	21-32	14-26	20-34	18-36	13 - 36	13 - 36
Einstellbereich [A/V]	25-150 A / 15-21 V	25-140 A / 15-21 V / 50-180 A / 16-23 V	25-180 A / 15-22,5 V	25-200 A / 15-24 V	15-200 A / 13-16 V	15-200 A / 13-16 V
Schweißstrom ED [A/%]	60 A/100% - 150 A/25 %	140 A/35% - 180 A/25 %	90 A/100% - 180 A/25 %	100 A/100% - 200 A/35 %	125A/100% - 200A/35%	125A/100% - 200A/35%
Drahtdurchmesser [mm]	0.6 - 0.8	- 0.8 (1,0)	0.6 - 0.8	0.6 - 0.8 (1.0)	0.6 - 0.8(1.0)	0.6 - 0.8(1.0)
Vorschub	KU 2-R	KU 2-R	AL 2-R	AL 2-R	AL 2-Rollen verzahnt	AL 2-Rollen verzahnt
Brenner	Zentr. 14	Zentr. 14	Zentr. 14	Zentr. 15	2 x Zentr. 15	3 x Zentr. 15
Kühlart	F	F	F	F	F	F
Isolierklasse	F	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21	21
Maße ca. (LxBxH) [mm]	810 x 325 x 560	810 x 325 x 560	810 x 325 x 560	810 x 325 x 560	870 x 420 x 820	870 x 420 x 820
Gewicht [kg]	44	50	47	50	60	67
Artikelnummer	01112 01113	01593 01595	21005 21006	01581 01587	S1572	20253