



TYP	550/15/250	750/15/350	950/15/350	950/15/500
Ansaugleistung [l/min]	550	750	950	950
Ansaugleistung [m³/min]	45	45	57	57
Druck, max. [bar]	15	15	15	15
Behältervolumen [Ltr]	350	350	350	500
Zylinder/Stufe [Zyl./St.]	2/2	2/2	2/2	2/2
Netzspannung [V / Ph. 50Hz]	400/3	400/3	400/3	400/3
Motorleistung [kW / HP]	5,5 / 7,5	5,5 / 7,5	7,5 / 10	7,5 / 10
Drehzahl [U/min]	1175	1275	925	925
Maße (lxbxh) [cm]	40x55x107	190x55x107	190x60x107	190x60x133
Artikelnummer	04121	04123	04125	04126

**D+L
TECHNIK**



TYP	700/11/150	700/11/270	900/11/270	900/11/350	1350/11/350	1350/11/500	550/15/270	750/15/270	950/16/270	950/16/500
Ansaugleistung [l/min]	700	700	900	900	1350	1350	550	750	950	950
Ansaugleistung [m³/min]	42	42	54	54	81	81	45	45	57	57
Druck, max. [bar]	11	11	11	11	11	11	15	15	15	1615
Behältervolumen [Ltr]	150	270	270	350	350	500	270	270	270	500
Zylinder/Stufe [Zyl./St.]	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2
Netzspannung [V / Ph. 50Hz]	400/3	400/3	400/3	400/3	400/3	400/3	400/3	400/3	400/3	400/3
Motorleistung [kW / HP]	4,0 / 5,5	4,0 / 5,5	5,5 / 7,5	5,5 / 7,5	7,5 / 10	7,5 / 10	5,5 / 7,5	5,5 / 7,5	7,5 / 10	7,5 / 10
Drehzahl [U/min]	1540	1540	1530	1530	1310	1310	1275	975	925	925
Maße (lxbxh) [cm]	55x72x165	55x72x180	60x74x185	Variabel	Variabel	Variabel	60x72x180	60x74x190	60x74x195	Variabel
Artikelnummer	04855	04865	04870	04871	04876	04877	04130	04128	04129	04136