



TYP	M K W 320/60   320/60-IP	M K W 350/35   350/35-IP	DIGI-MIG MKW 350/35	MKW 350/60   350/60-IP DIGI-MIG MKW 50/60	M K W   DIGI-MIG MKW 450/60   450/60-IP
Netzspannung [V/Hz]	400/50	400/50	400/50	400/50	400/50
Netzabsicherung [A]	20	25	25	25	30
Einstellungen	2 x 7	4 x 7	4 x 7	4 x 7	4 x 7
Leerlaufspannung [V]	18 - 46	20 - 49	20 - 49	20 - 49	20 - 50
Einstellbereich [A/V]	30-320 A/16-30 V	40-400 A/16-33 V	40-400 A/16-33 V	45-400 A/16-33 V	50-500 A/16,5-35 V
Schweißstrom ED [A/%]	220 A/100% - 320 A/60 %	230 A/100% - 350 A/35%	230 A/100% - 350 A/35 %	260 A/100% - 350 A/60 %	300 A/100% - 450 A/60 %
Drahtdurchmesser [mm]	(0,6) 0,8 - 1,2	0,8 - 1,2	0,8 - 1,6	0,8 - 1,6	0,8 - 1,6
Vorschub	Al 2-Rollen verzahnt	Al 2-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt
Brenner	Zentr. 401	Zentr. 401	Zentr. 401	Zentr. 401	Zentr. 401
Kühlart	F	F	F	F	F
Isolierklasse	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21
Maße [mm]	870 x 420 x 1300	870 x 420 x 1300	920 x 520 x 1300	920 x 520 x 1300	920 x 520 x 1300
Gewicht [kg]	150	160	170	180	190
Artikelnummer	21060   21061	21065   21066	21475	21070   21071	21075   21076